

## 22" Standard Signage

22SM3G-B

### Key Features

- Brightness(Typ.) : 250 cd/m<sup>2</sup>
- Bezel : 16.3mm
- Depth : 53.8mm
- Interface : HDMI(2) / USB 2.0 / RS232C / RJ45 / IR / Audio
- USB Plug & Play, Built-in Wi-Fi



## All Spec

### PANEL

Screen Size  
21.5"

Native Resolution  
1,920 x 1,080 (FHD)

Contrast Ratio  
1,000:1

Color gamut  
BT.709 95%

Color Depth  
6bit, 16.7Million Colors

Surface Treatment(Haze)  
25%

Portrait / Landscape  
No / Yes

Panel Technology  
IPS

Brightness  
250 nit (Typ.)

Dynamic CR  
400,000:1

Viewing Angle(H x V)  
178 X 178

Response Time  
14ms (G to G)

Operation Hours (Hours/Day)  
16/7

### CONNECTIVITY

Input - Digital - HDMI  
Yes(2), HDCP2.2

Input - External Control - RS232C IN  
Yes(1), Phone-jack

Input - External Control - IR IN  
Yes(1), Phone-jack

Input - Audio In  
Yes(1)

Input - External Control - RJ45(LAN)  
Yes(1)

Input - USB  
USB2.0 Type A(1)

## MECHANICAL SPECIFICATION

---

Bezel Color

Black

Bezel Width

Even Bezel 16.3mm

Weight(Head)

3.34 kg

Monitor Dimension(W x H x D)

510.3 x 302.1 x 53.8mm

VESA™ Standard Mount Interface

100 x 100

## ENVIRONMENT CONDITIONS

---

Operation Temperature

0 °C to 40 °C

Operation Humidity

10 % to 80 %

## POWER

---

Power Supply

AC 100-240V~, 50/60Hz

Power Type

Built-In Power

## SOUND

---

Speaker

Yes(1W x 2EA)

## ACCESSORY

---

Basic

Remote Controller, Power Cord, QSG, HDMI Cable,  
Phone to RS232C Gender, External IR, IR Sheet

## KEY FEATURE

---

HW - Internal Memory

8GB

HW - Wi-Fi - Built-in

Yes

HW - Sensor - Temperature Sensor

Yes

HW - Local Key Operation

Yes

SW - webOS ver.

webOS 4.1

SW - Embedded CMS - Local Contents Scheduling

Yes

SW - Embedded CMS - Group Manager

Yes

SW - USB Plug & Play

Yes

SW - Fail over

Yes

SW - Background Image - Booting Logo Image

Yes

SW - Background Image - No Signal Image

Yes

SW - Multi-screen - PIP

Yes

SW - Multi-screen - PBP

Yes(2)

SW - Screen Share

Yes

SW - Video Tag

Yes(2)

SW - Gapless Playback

Yes

SW - SNMP

Yes

SW - Status Mailing

Yes

SW - 3rd Party Compatibility - Crestron Connected&lt;sup&gt;®&lt;/sup&gt;

Yes (Network Based Control)

SW - PM mode

Yes

SW - Beacon

Yes

SW - SI Server Setting

Yes

SW - Pro:Idiom

Yes

SW - Play via URL

Yes

SW - Setting Data Cloning

Yes

SW - ISM Method

Yes

SW - Control Manager

Yes

SW - Smart Energy Saving

Yes

SW - Wake on LAN

Yes

SW - HDMI-CEC

Yes (Compatibility may differ by equipment.)

SW - webRTC

Yes

## POWER CONSUMPTION

---

Typ.

30W

Max.

33W

BTU (British Thermal Unit)

7.17(Typ), 7.89(Max)

## CERTIFICATION

---

Safety

CB / NRTL

EMC

FCC Class "A" / CE

ErP

Yes (EU Only)

## SOFTWARE COMPATIBILITY

---

SuperSign CMS

Yes

SuperSign Control / Control+

Yes / Yes

SuperSign WB

Yes

SuperSign Media Editor

Yes

Signage 365 Care

Yes (The availability can differ by region.)